Revision Date 03-05-2015 Revision Number 1



SECTION 1 Identification of the substance/mixture and of the company/undertaking

Product identification used on label

Product identifier 3076

Details of the supplier of the safety

data sheet

TECTYL 283S17HF
Daubert Chemical Company
4700 S. Central Avenue

Chicago, IL 60638 708-496-7350

Emergency telephone number Relevant identified uses of the substance or mixture and uses

advised against

Chemtrec: (800) 424-9300 Corrosion Preventive Compound

SECTION 2 Hazards identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols





GHS Aspiration Hazard Category 1
Classification Skin Corrosion/Irritation Category 2

Serious Eye Damage/Eye Irritation Category 2B

Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

Flammable Liquid Category 4

Acute Toxicity - Inhalation Vapour Category 4

Signal Word Danger

Hazard Combustible Liquid

Statements May be fatal if swallowed and enters airways.

Causes skin and eye irritation

Harmful if inhaled.

May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary Statements

Prevention Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

TECTYL 283S17HF Page 1 of 6

Revision Date 03-05-2015 **Revision Number 1**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Response

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable

for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

Call a POISON CENTER or doctor/physician if you feel unwell.

Specific treatment: None known

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Use dry chemical, water fog, CO2, foam or sand/earth for extinction.

Store in a well-ventilated place. Keep container tightly closed. Storage

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with Disposal

local/regional/national/international regulation for hazardous wastes.

SECTION 3 Composition/information on ingredients

| Chemical Name | CAS# | % | |
|---|------------|---------|--|
| Hydrotreated light distillate (Petroleum) | 64742-47-8 | 90 - 99 | |
| Ethylene glycol mono-n-butyl ether | 111-76-2 | 0.1 - 1 | |

Note: Specific chemical identities and/or exact percentages have been withheld as a trade secret.

SECTION 4 First aid measures

| Inhalation | If symptoms are experienced remove source of contamination or move victim to fresh air and obtain medical advice. |
|----------------|---|
| Eyes | Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention. |
| Skin Contact | Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists. |
| Ingestion | Do not induce vomiting and seek medical attention immediately. Provide medical care provider with this SDS. |
| Note to Doctor | Treat symptomatically. |

SECTION 5 Firefighting measures

Extinguishing media Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray when

fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the fire. Do not direct

a water stream directly into the hot burning liquid.

Material may be ignited if preheated to temperatures above the flash Fire and/or Explosion Hazards

point in the presence of a source of ignition. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that

may lead to injury or death.

TECTYL 283S17HF Page 2 of 6

Revision Date 03-05-2015 Revision Number 1

Fire Fighting Methods and Protection

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Use appropriate methods for the surrounding fire.

Hazardous Combustion Products

Carbon dioxide, Carbon monoxide, Hydrocarbons

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Methods and materials for containment and cleaning up

Absorb or cover with dry earth, sand or other non-combustible material and transfer to appropriate waste containers. Use clean, non-sparking tools to collect absorbed material. Collect and discard in accordance with local, state and national regulations.

SECTION 7 Handling and storage

Precautions for safe handling

Avoid contacting and avoid breathing the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous.

Conditions for safe storage, including any incompatibilities

Store in a cool dry place. Isolate from incompatible materials. Keep container closed when not in use. Keep away from heat, sparks, and flame.

Incompatible materials

Strong oxidizing agents, Strong alkalies, Acids

SECTION 8 Exposure controls/personal protection

Control parameters

<u>Chemical Name</u> <u>ACGIH TLV</u> <u>ACGIH STEL</u> <u>OSHA PEL</u>

Hydrotreated light distillate (Petroleum) 212 ppm (8 hrs)

This product contains mineral oils having recommended exposure limits of 5 mg/m3 in mist form. Because the viscosity of this product is <= 20.5 cSt, mists can be formed in certain applications. If mists do form, use appropriate controls to maintain exposure below the stated limits.

Engineering Measures

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits

TECTYL 283S17HF Page 3 of 6

Revision Date 03-05-2015 Revision Number 1

Respiratory Protection Proper ventilation (at a minimum) will be required when handling this product. Use

respirators (NIOSH approved) only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work

place conditions warrant the use of a respirator.

Eye Protection Wear chemically resistant safety glasses with side shields when handling this product.

Do not wear contact lenses.

Skin Protection Wear protective gloves. Inspect gloves for chemical break-through and replace at

regular intervals. Clean protective equipment regularly. Wash hands and other exposed

areas with mild soap and water before eating, drinking, and when leaving work.

Gloves Chemically resistant gloves

SECTION 9 Physical and chemical properties (Typical, not specification)

Physical State Liquid Color Amber

Odor Slight Solvent Odor **Odor Threshold** No data available No data available pΗ Melting Point, °C No data available Boiling Point, °C No data available **Flash Point** 152 °F(67 °C) **Evaporation Rate** No data available Flammability (Solid, Gas) No data available Lower Flammable/Explosive Limit, No data available

% in air

Upper Flammable/Explosive Limit, No data available

% in air

Vapor Pressure 0.5 mmHg
Vapor Density >1 (Air=1)
Specific Gravity @ 25°C 0.81

Solubility in WaterNegligible; 0-1%Octanol/Water Partition CoefficientNo data availableAutoignition TemperatureNo data availableDecomposition TemperatureNo data availableViscosity5 cSt @ 40°C

Volatiles, % by weight 83 VOC, lb/gal 5.6 VOC, grams/liter 671.7

SECTION 10 Stability and reactivity

Chemical stability Stable under normal conditions. Hazardous polymerization

will not occur.

Possibility of hazardous reactions Under normal conditions of storage and use, hazardous

reactions will not occur.

Conditions to avoid Contamination. Elevated temperatures.

Incompatible materials Strong oxidizing agents, Strong alkalies, Acids

Hazardous decomposition productsDecomposition and hazardous decomposition products are

unlikely.

TECTYL 283S17HF Page 4 of 6

Revision Date 03-05-2015 Revision Number 1

SECTION 11 Toxicological information

Likely Routes of Entry Inhalation, Skin contact, Eye contact

Target Organs Potentially Affected by Exposure Central Nervous System

Chemical Interactions That Change Toxicity

No chemical interaction known to affect toxicity.

Medical Conditions Aggravated Skin contact may aggravate existing skin disease, Respiratory

disease including asthma and bronchitis

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and

headache. Other possible symptoms include; wheezing and coughing due to pulmonary

edema (fluid build-up in lungs).

Inhalation Toxicity Non-Toxic. Not known to cause systemic damage.

Skin Contact Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause

permanent damage.

Skin Absorption No absorption hazard expected in normal industrial use.

Eye Contact Can cause moderate irritation, tearing and reddening, but not likely to permanently injure

eye tissue.

Ingestion Irritation Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea,

vomiting and diarrhea. Substance is harmful if swallowed. Large exposure may be fatal.

Ingestion Toxicity Harmful if swallowed.

Long-Term (Chronic) Health Effects

Carcinogenicity Not listed by ACGIH, IARC, NIOSH, NTP OR OSHA.

Reproductive and Developmental Toxicity No data available to indicate product or any components present at

greater than 0.1% may cause birth defects.

Inhalation Upon prolonged and/or repeated exposure, can cause severe respiratory irritation,

dizziness, weakness, fatigue, nausea, headache and possible unconsciousness. Can cause

systemic damage upon prolonged and/or repeated exposure (see "Target Organs)

Skin Contact Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and

dermatitis.

Skin Absorption Upon prolonged or repeated exposure, no hazard in normal industrial use.

Component Toxicology Data

Chemical Name CAS Number LD50/LC50

No data available

SECTION 12 Ecological information

Overview No ecological information available

MobilityNo dataPersistenceNo dataBioaccumulationNo dataDegradabilityNo data

Ecotoxicity Data

Chemical Name CAS Number Aquatic EC50 Aquatic ERC50 Aquatic LC50

Crustacea Algae Fish

No data available

TECTYL 283S17HF Page 5 of 6

Revision Date 03-05-2015 Revision Number 1

SECTION 13 Disposal considerations

Waste Description for Spent Product Spent or discarded material may be a hazardous waste.

Disposal MethodsDispose of by incineration following Federal, State, Local, or Provincial

regulations.

Waste Disposal Code(s) D001

SECTION 14 Transport information

Full Shipping Name for UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent), 3, PG III

Export, Air, Sea (any

quantity) or vessels of 119 gal.

or more:

Domestic Ground in vessels < Not Regulated

119 gal.

SECTION 15 Regulatory information

TSCA Status All components in this product are on the TSCA Inventory or exempt.

Canadian DSL One or more chemical substances in this material are on the Canadian NDSL and the remainder

status: are included on the Canadian DSL or are exempt.

Chemical Name CAS # Regulation Percent

No 313-listed chemicals in this product SARA 313

SECTION 16 Other information

Revision 03-05-2015

Date

Disclaimer Although the information contained herein is believed to be reliable, it is furnished without warranty

of any kind. This information is not intended to be all-inclusive as to the manner and conditions of

use, handling, and storage.

Version Original

Comments Approved: J. Kump / M. Duncan

TECTYL 283S17HF Page 6 of 6