Revision Date 03-10-2015 **Revision Number 3**



SECTION 1 Identification of the substance/mixture and of the company/undertaking

Product identification used on label

Product identifier 3009

TECTYL 506

Details of the supplier of the safety

data sheet

Daubert Chemical Company 4700 S. Central Avenue

Chicago, IL 60638 708-496-7350

Emergency telephone number Relevant identified uses of the

substance or mixture and uses

advised against

Chemtrec: (800) 424-9300 Corrosion Preventive Compound

SECTION 2 Hazards identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols







GHS Aspiration Hazard Category 1 Classification Skin Corrosion/Irritation Category 2

Serious Eye Damage/Eye Irritation Category 2B

Flammable Liquid Category 3

Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

Acute Toxicity - Inhalation Vapour Category 4

Signal Word Danger

Flammable liquid and vapour. Hazard

May be fatal if swallowed and enters airways. Statements

Causes skin and eye irritation

Harmful if inhaled.

May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary Statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Prevention

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof equipment. Use only non-sparking tools.

Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

TECTYL 506 Page 1 of 6

Revision Date 03-10-2015 Revision Number 3

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable

for breathing.

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

Call a POISON CENTER or doctor/physician if you feel unwell.

Specific treatment: None known Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Use dry chemical, water fog, CO2, foam or sand/earth for extinction.

Storage Keep container tightly closed.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal Dispose of contents/container in accordance with

local/regional/national/international regulation for hazardous wastes.

SECTION 3 Composition/information on ingredients

Chemical Name	CAS#	%
Hydrotreated light distillate (Petroleum)	64742-47-8	10 - 30
Stoddard solvent	8052-41-3	10 - 30

Note: Specific chemical identities and/or exact percentages have been withheld as a trade secret.

SECTION 4 First aid measures

Inhalation	If symptoms are experienced remove source of contamination or move victim to fresh air and obtain medical advice.
Eyes	Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.
Skin Contact	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.
Ingestion	Do not induce vomiting and seek medical attention immediately. Provide medical care provider with this SDS.
Note to Doctor	Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media	Use alcohol resistant foam, carbon dioxide, or dry chemical
	extinguishing agents. Water may be ineffective but water spray can be
	used extinguish a fire if swept across the base of the flames. Water can
	absorb heat and keep exposed material from being damaged by fire.

TECTYL 506 Page 2 of 6

Revision Date 03-10-2015 Revision Number 3

Fire and/or Explosion Hazards

Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death.

Fire Fighting Methods and Protection

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

Hazardous Combustion Products

Carbon dioxide, Carbon monoxide, Sulfur compounds, Hydrocarbons

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill. Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

Methods and materials for containment and cleaning up

SECTION 7 Handling and storage

Precautions for safe handling

Avoid contacting and avoid breathing the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Store in a cool dry place. Isolate from incompatible materials. Keep container closed when not in use. Keep away

Conditions for safe storage, including any incompatibilities

Incompatible materials

from sources of ignition. Strong oxidizing agents, Strong alkalies, Acids

TECTYL 506 Page 3 of 6

Revision Date 03-10-2015 Revision Number 3

SECTION 8 Exposure controls/personal protection

Control parameters			
<u>Chemical Name</u>	ACGIH TLV	ACGIH STEL	OSHA PEL

Hydrotreated light distillate (Petroleum) 212 ppm (8 hrs)

 Stoddard solvent
 100 ppm TWA; 525 mg/m3 TWA
 500 ppm TWA; 2900 mg/m3 TWA

Engineering Measures Local exhaust ventilation or other engineering controls are normally required when

handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne

levels below recommended exposure limits

Respiratory Protection Proper ventilation (at a minimum) will be required when handling this product. Use

respirators (NIOSH approved) only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work

place conditions warrant the use of a respirator.

Eye Protection Wear chemically resistant safety glasses with side shields when handling this product.

Do not wear contact lenses.

Skin Protection Wear protective gloves. Inspect gloves for chemical break-through and replace at

regular intervals. Clean protective equipment regularly. Wash hands and other exposed

areas with mild soap and water before eating, drinking, and when leaving work.

Gloves Chemically resistant gloves

SECTION 9 Physical and chemical properties (Typical, not specification)

Physical State Liquid Color Amber

Odor Slight Solvent Odor **Odor Threshold** No data available No data available рH Melting Point, °C No data available Boiling Point, °C No data available **Flash Point** $>= 100 \, {}^{\circ}\text{F}(38 \, {}^{\circ}\text{C})$ **Evaporation Rate** No data available Flammability (Solid, Gas) No data available Lower Flammable/Explosive Limit, No data available

% in air

Upper Flammable/Explosive Limit, No data available

% in air

Vapor Pressure 2 mmHg Vapor Density >1 (Air=1) Specific Gravity @ 25°C 0.86

Solubility in WaterNegligible; 0-1%Octanol/Water Partition CoefficientNo data availableAutoignition TemperatureNo data available

TECTYL 506 Page 4 of 6

Revision Date 03-10-2015 **Revision Number 3**

No data available **Decomposition Temperature** No data available Viscosity

Volatiles, % by weight 44 VOC, lb/gal 3.21 VOC, grams/liter 385 **VOC** minus exempt solvents & water, 3.21

lb/gal

SECTION 10 Stability and reactivity

Chemical stability Stable under normal conditions. Hazardous polymerization

will not occur.

Possibility of hazardous reactions Under normal conditions of storage and use, hazardous

reactions will not occur.

Contamination. Elevated temperatures. Conditions to avoid

Incompatible materials Strong oxidizing agents, Strong alkalies, Acids

Hazardous decomposition products Decomposition and hazardous decomposition products are

unlikely.

SECTION 11 Toxicological information

Likely Routes of Entry Inhalation, Skin contact, Eye contact

Target Organs Potentially Affected by Exposure Central Nervous System, Respiratory Tract, Skin, Eyes,

Kidneys, Liver, Nervous System

Chemical Interactions That Change Toxicity

No chemical interaction known to affect toxicity.

Medical Conditions Aggravated Skin contact may aggravate existing skin disease, Respiratory

disease including asthma and bronchitis

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and

headache. Other possible symptoms include; wheezing and coughing due to pulmonary

edema (fluid build-up in lungs).

Skin Contact Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause

permanent damage.

Eye Contact Can cause moderate irritation, tearing and reddening, but not likely to permanently injure

eve tissue.

Ingestion Irritation Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea,

vomiting and diarrhea. Substance is harmful if swallowed. Large exposure may be fatal.

Ingestion Toxicity Harmful if swallowed.

Long-Term (Chronic) Health Effects

Not listed by ACGIH, IARC, NIOSH, NTP OR OSHA. Carcinogenicity

Reproductive and Developmental Toxicity No data available to indicate product or any components present at

greater than 0.1% may cause birth defects.

Upon prolonged and/or repeated exposure, can cause severe respiratory irritation, Inhalation

dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.

Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and **Skin Contact**

dermatitis. Not likely to cause permanent damage.

Page 5 of 6 TECTYL 506

Revision Date 03-10-2015 Revision Number 3

Component Toxicology Data

Chemical Name CAS Number LD50/LC50

Stoddard solvent 8052-41-3 Oral LD50 Rat > 5000 mg/kg Inhalation LC50 (4h) Rat > 5500

MG/CU M

SECTION 12 Ecological information

Overview No ecological information available

MobilityNo dataPersistenceNo dataBioaccumulationNo dataDegradabilityNo data

Ecotoxicity Data

Chemical Name CAS Number Aquatic EC50 Aquatic ERC50 Aquatic LC50

Crustacea Algae Fish

No data available

SECTION 13 Disposal considerations

Waste Description for Spent Product Spent or discarded material is a hazardous waste.

Disposal Methods Dispose of by incineration following Federal, State, Local, or Provincial

regulations.

Waste Disposal Code(s) D001

SECTION 14 Transport information

Full Shipping Name for UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent), 3, PG III

Export, Air, Sea (any

quantity) or vessels of 119 gal.

or more:

Domestic Ground in vessels < Not Regulated

119 gal.

SECTION 15 Regulatory information

TSCA Status All components in this product are on the TSCA Inventory or exempt.

Canadian DSL All chemical substances in this material are included on or exempted from listing on the

status: Canadian DSL.

Chemical Name CAS # Regulation Percent

No 313-listed chemicals in this product SARA 313

SECTION 16 Other information

Revision 03-10-2015

Date

Disclaimer Although the information contained herein is believed to be reliable, it is furnished without warranty

of any kind. This information is not intended to be all-inclusive as to the manner and conditions of

use, handling, and storage.

Version Revised

Comments Approved: J. Kump / M. Duncan

TECTYL 506 Page 6 of 6