Revision Date 03-10-2015 Revision Number 2



SECTION 1 Identification of the substance/mixture and of the company/undertaking

Product identification used on label

Product identifier 3018

TECTYL 714

Details of the supplier of the safety

data sheet

Daubert Chemical Company 4700 S. Central Avenue Chicago, IL 60638

708-496-7350

Emergency telephone number Relevant identified uses of the substance or mixture and uses

advised against

Chemtrec: (800) 424-9300 Corrosion Preventive Compound

SECTION 2 Hazards identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Classification Not classified as hazardous under

OSHA.

Hazard Statements Not hazardous under OSHA regulations.

SECTION 3 Composition/information on ingredients

Chemical NameCAS #%Hydrotreated middle distillate64742-46-77 - 15

Note: Specific chemical identities and/or exact percentages have been withheld as a trade secret.

SECTION 4 First aid measures

| T 1 1 14 | TC . | | | С. | | • .• . | C 1 | |
|------------|-----------------|-------------|-------------|------------|--------------|-----------------|---------|---------|
| Inhalation | If symptoms are | experienced | remove sour | ce of cont | amınatıon oı | r move victim t | o fresh | air and |

obtain medical advice.

Eyes Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often.

Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate

medical attention and monitor the eye daily as advised by your physician.

Skin Contact Wash with soap and water. Remove contaminated clothing and launder. Get medical attention

if irritation develops or persists.

Ingestion Do not induce vomiting and seek medical attention immediately. Provide medical care

provider with this SDS.

Note to Doctor Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing mediaUse alcohol resistant foam, carbon dioxide, or dry chemical when

fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do Not direct a stream of water into the hot burning liquid. Use water fog, foam, dry chemical or carbon dioxide (CO2) to

extinguish flames.

TECTYL 714 Page 1 of 5

Revision Date 03-10-2015 Revision Number 2

Fire and/or Explosion Hazards Mater

Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death

Fire Fighting Methods and Protection

Do not enter fire area without proper protection including selfcontained breathing apparatus and full protective equipment. Use appropriate methods for the surrounding fire.

Hazardous Combustion Products Hydro

Hydrocarbons, Oxides of carbon

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Methods and materials for containment and cleaning up

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

SECTION 7 Handling and storage

Precautions for safe handling

Avoid contacting and avoid breathing the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Remove contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Store in a cool dry place. Isolate from incompatible materials. Store in tightly sealed original container. Keep away from heat, sparks, and flame.

Incompatible materials

Strong oxidizing agents

SECTION 8 Exposure controls/personal protection

Control parameters

<u>Chemical Name</u> <u>ACGIH TLV</u> <u>ACGIH STEL</u> <u>OSHA PEL</u>

Hydrotreated middle distillate 5 mg/m3 (oil mist) 10 mg/m3 (oil mist) 5 mg/m3 (oil mist)

This product contains mineral oils having recommended exposure limits of 5 mg/m3 in mist form. Because the viscosity of this product is \leq 20.5 cSt, mists can be formed in certain applications. If mists do form, use appropriate controls to maintain exposure below the stated limits.

TECTYL 714 Page 2 of 5

Revision Date 03-10-2015 Revision Number 2

Engineering Measures Local exhaust ventilation or other engineering controls are normally required when

handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits Facilities storing or using this material

should be equipped with an eyewash and safety shower.

Respiratory Protection Respiratory protection may be required to avoid overexposure when handling this

product. General or local exhaust ventilation is the preferred means of protection. Use a

respirator if general room ventilation is not available or sufficient to eliminate symptoms. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator. Wear a NIOSH approved respirator if any exposure is possible.

Eye Protection Wear chemically resistant safety glasses with side shields when handling this product.

Do not wear contact lenses.

Skin Protection Wear protective gloves. Inspect gloves for chemical break-through and replace at

regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. When handling material that has been heated, wear chemically resistant thermally insulating gloves, chemical resistant apron, long sleeves and other clothing as necessary to protect

against thermal burns.

Gloves Chemically resistant gloves

SECTION 9 Physical and chemical properties (Typical, not specification)

Physical State Liquid Color Amber

Slight Solvent Odor Odor **Odor Threshold** No data available No data available Hq No data available Melting Point, °C Boiling Point, °C No data available **Flash Point** $> 275 \, ^{\circ}\text{F}(135 \, ^{\circ}\text{C})$ **Evaporation Rate** No data available Flammability (Solid, Gas) No data available Lower Flammable/Explosive Limit, No data available

% in air

Upper Flammable/Explosive Limit, No data available

% in air

Vapor Pressure < 0.06 mmHg

Specific Gravity @ 25°C 0.9 **Solubility in Water** Insoluble

Octanol/Water Partition CoefficientNo data availableAutoignition TemperatureNo data availableDecomposition TemperatureNo data availableViscosity19 cSt @ 40°CVolatiles, % by weightNo data available

VOC, lb/gal 2.18 VOC, grams/liter 261.5

TECTYL 714 Page 3 of 5

Revision Date 03-10-2015 Revision Number 2

SECTION 10 Stability and reactivity

Chemical stability Stable under normal conditions. Hazardous polymerization

will not occur.

Possibility of hazardous reactionsUnder normal conditions of storage and use, hazardous

reactions will not occur.

Conditions to avoid Contamination.

Incompatible materials Strong oxidizing agents

Hazardous decomposition productsDecomposition and hazardous decomposition products are

unlikely.

SECTION 11 Toxicological information

Likely Routes of EntryInhalation, Skin contact, Eye contact **Target Organs Potentially Affected by Exposure**Kidneys, Liver, Respiratory Tract, Skin

Chemical Interactions That Change Toxicity

No chemical interaction known to affect toxicity.

Medical Conditions Aggravated Skin contact may aggravate existing skin disease

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and

headache.

Inhalation Toxicity Can cause systemic damage (see "Target Organs)

Skin Contact Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause

permanent damage.

Skin Absorption No absorption hazard expected in normal industrial use.

Eye Contact Can cause moderate irritation, tearing and reddening, but not likely to permanently injure

eve tissue.

Ingestion Irritation Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea,

vomiting and diarrhea.

Ingestion Toxicity Harmful if swallowed.

Long-Term (Chronic) Health Effects

Carcinogenicity Not listed by ACGIH, IARC, NIOSH, NTP OR OSHA.

Reproductive and Developmental Toxicity No data available to indicate product or any components present at

greater than 0.1% may cause birth defects.

Inhalation Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation,

dizziness, weakness, fatigue, nausea and headache. Can cause systemic damage upon

prolonged and/or repeated exposure (see "Target Organs)

Skin Contact Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and

dermatitis. Not likely to cause permanent damage.

Skin Absorption Upon prolonged or repeated exposure, no hazard in normal industrial use.

Component Toxicology Data

Chemical Name CAS Number LD50/LC50

Hydrotreated middle distillate 64742-46-7 Dermal LD50 Rabbit > 2000 mg/kg Oral LD50 Rat > 5000 mg/kg

Inhalation LC50 (1h) Rat = 7 mg/L

SECTION 12 Ecological information

Overview No ecological information available

MobilityNo dataPersistenceNo dataBioaccumulationNo dataDegradabilityNo data

TECTYL 714 Page 4 of 5

Revision Date 03-10-2015 Revision Number 2

Ecotoxicity Data

Chemical Name CAS Number Aquatic EC50 Aquatic ERC50 Aquatic LC50 Crustacea Algae Fish

No data available

SECTION 13 Disposal considerations

Waste Description for Spent Product Spent or discarded material is not expected to be a hazardous waste.

Disposal MethodsDispose of in accordance with Local and National regulations.

Waste Disposal Code(s) Not applicable

SECTION 14 Transport information

Full Shipping Name for Rust Inhibitor / Non-Hazardous

Export, Air, Sea (any

quantity) or vessels of 119 gal.

or more:

Domestic Ground in vessels < Not Regulated

119 gal.

SECTION 15 Regulatory information

TSCA Status All components in this product are on the TSCA Inventory or exempt.

Canadian DSL All chemical substances in this material are included on or exempted from listing on the

status: Canadian DSL.

Chemical Name CAS # Regulation Percent

No 313-listed chemicals in this product SARA 313

SECTION 16 Other information

Revision 03-10-2015

Date

Disclaimer Although the information contained herein is believed to be reliable, it is furnished without warranty

of any kind. This information is not intended to be all-inclusive as to the manner and conditions of

use, handling, and storage.

Version Revised

Comments Approved: J. Kump / M. Duncan

TECTYL 714 Page 5 of 5