



## PERFORMANCE PLUS® R&O OILS

**PERFORMANCE PLUS® R&O Oils** contain rust and oxidation inhibition (R&O) chemistry in a high paraffinic, high saturates base oil. These oils are highly suitable for use in circulating and hydraulic systems where oils are used for long periods of time. In addition to the rust and oxidation inhibition, these oils also exhibit excellent water demulsibility and anti-foam characteristics.

### Features and Benefits

- Provide superior service in industrial gear applications requiring rust and oxidation inhibited lubricants.
- Limit fluid oxidation, protects seals, permits quick fluid/water separation, and controls foaming during severe agitation.

### Applications

Performance Plus R&O OILS can be used in both mobile and stationary hydraulic equipment as well as applications requiring an R&O oil for gear box and speed reducer lubrication, giving service flexibility and minimized lubricant inventory. Additional uses are airline lubricators, vacuum pumps, select heat transfer, turbines, as well as general lubrication applications where R&O (rust and oxidation inhibited) oils are specified.

The foundation of Performance Plus Oils are Kleen Performance Products hydro-treated high VI base oils.

### TYPICAL PROPERTIES

ECOPOWER®	ISO VG	22	32	46	68	100	150	220
Color		L 1.0	L 1.0	L 1.5	L 2.5	L 3.0	L 5.0	L 5.5
Specific Gravity (60°F)		0.855	0.856	0.859	0.865	0.876	0.879	0.882
Kinematic Viscosity								
cSt @ 40°C		22.1	32.2	43.5	65.9	94.7	144.5	209.4
cSt @ 100°C		4.4	5.6	6.8	9.0	11.1	14.7	18.8
Viscosity Index		106	112	113	112	102	101	100
Flash Point, °C		204	222	244	250	256	260	264
Pour Point, °C		-39	-33	-33	-30	-18	-12	-9
Water Separability (@ 30 min)		40/40/0	40/40/0	40/40/0	40/40/0	40/40/0	40/40/0	40/40/0
MAG Approvals		-	P-38	P-55	P-54	-	-	-

Note: Values shown above are representative of current production and may vary within modest ranges.

Rev. 06/16