

SurStik® MULTISERVICE LUBRICANT

Whitmore's new SurStik® Multiservice Lubricant is designed with the latest technology available in nontoxic, nonheavy metal, extreme pressure/antiwear chemistry. The unique design of this revolutionary new product includes severely hydrotreated base stocks, an advanced polymerized thickener system, and Whitmore's unique Bi-Laminate™ additive system. Whitmore's SurStik® is specially formulated for use on mining shovels and draglines in open cut operations to reduce the adverse effects of severe dust and dirt contamination, water, ice and snow, and changes in temperature.

Whitmore's SurStik® contains a high molecular weight polymer that resists drying, oxidation, and thermal decomposition. This is extremely helpful in areas of high dust contamination or when typical weather conditions can cause peeling and "flaking" of conventional lubricants from sticks, gears, and circle rails. Whitmore's Bi-Laminate™ additive system provides superior load-carrying ability and high performance wear resistance in an environmentally safe package.

Whitmore's SurStik® has a thickener structure that inherently resists emulsification with water and has excellent mechanical and thermal stability. This thixotropic structure makes the product ideal for use in bearings and bushings. Field results indicate that the product's performance increases as operating and climatic conditions become more severe. The low temperature capabilities allow the lubricant film to maintain its adhesive characteristics and durable protection under the most demanding conditions.

BENEFITS:

- **EXTREME LOAD-CARRYING ABILITY** - protects during shock loading against seizure.
- **VERSATILE** - superior mechanical stability and shear resistance allow the product to be used in a variety of applications including open gears, sticks, circle rail and rollers, antifriction bearings, and bushings.
- **ENVIRONMENTAL COMPLIANCE** - free of heavy metals and solvents.
- **WIDE TEMPERATURE RANGE** - use SurStik® Summer year-round in warm climates. Use SurStik® Winter year-round in northern climates.

APPLICATIONS:

Whitmore's SurStik® is highly recommended for applications on mining shovels and draglines including open gears, sticks, circle rails and rollers, lower swing bearings, and bushings. Whitmore's SurStik® meets or exceeds the lubricant specification of major OEM's for a multiservice lubricant.

SurStik® is also highly recommended for the open gears of kilns and driers.

ASTM #		TYPICAL CHARACTERISTICS		
		Winter Grade	Summer Grade	Extra Heavy Grade
	NLGI Grade	00 to 0	1	1 to 1.5
D-445	Kinematic Viscosity, base oil (Base Oil without Polymer)			
	cSt @ 40°C	46	1,500	1,500
	cSt @ 100°C	6.7	65	65
	(Base Oil with Polymer)			
	cSt @ 40°C	680	5,400	5,400
	cSt @ 100°C	51.2	195	195
Gardner Method	Density, lb/gal @ 60°F (15.5°C)	8.51	8.15	8.75
	Specific Gravity, g/cc @ 60°F (15.5°C)	1.022	0.979	1.050
D-2596	Four Ball EP			
	Weld Point, kg	500	620	500
	Load Wear Index	90	100	--
D-1743	Rust Test	Pass	Pass	Pass
D-4048 (Modified)	Copper Strip Corrosion for Greases 212°F (100°C) @ 3 hrs	1B	1B	1B
	Thickener Type	Aluminum Complex	Aluminum Complex	Aluminum Complex
OEM Standard	Low Temperature Pumpability Lincoln Ventmeter @ 400 psi, °F (°C)	-40 (-40)	10 (-12)	20 (-7)
	Operating Range, °F (°C)	-40 to 50 (-40 to 10)	10 to 170 (-12 to 75)	20 to 230 (-7 to 110)

The above are average values. Minor variations which do not affect product performance are to be expected in normal manufacturing.

PACKAGING

Shuttle Tanks	Drums	Kegs	Pails
---------------	-------	------	-------

930 Whitmore Drive • Rockwall, Texas 75087 • USA • (972) 771-1000 • 800-699-6318
An ISO 9001 and ISO 14001 registered company • www.whitmores.com

LIMITED WARRANTY: The Whitmore Manufacturing Company makes the Limited Express Warranty that at the date of delivery, its goods shall be free from defects in Whitmore's materials and workmanship and shall meet the express written statements of quality, if any, made by Whitmore in connection with the sale of the goods. Other than such Limited Express Warranty, there are no express warranties made with respect to the sale of goods and all implied warranties existing under the law are expressly disclaimed and negated, particularly, Whitmore NEGATES AND DISCLAIMS THE IMPLIED WARRANTY OF MERCHANTABILITY AND THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. All other liability, either in contract or tort, including without limitation, strict liability found in Section 402A of the Restatement of Torts or otherwise, is negated and disclaimed. The sole remedy for Whitmore's breach of such Limited Express Warranty shall be a refund of the purchase price of its goods, and Whitmore shall have no responsibility for incidental or consequential damages sustained as a result of the use of the goods, whether sustained to the goods themselves or to other property. Data listed are subject to usual manufacturing variations.

