# Product Information Specialty Lubricants

## **Dow Corning® 3179 Dilatant Compound**

#### **FEATURES & BENEFITS**

- Dilatant rheological properties
- High elasticity
- High bounce

#### **COMPOSITION**

• Filled silicone polymer

#### APPLICATIONS

 Primarily for the novelty toy market for use by children to bounce, stretch and snap

#### TYPICAL PROPERTIES (ALL VALUES IN TABLE)

Specification Writers: These values are not intended for use in preparing specifications. Please contact your local Dow Corning sales office or your Global Dow Corning Connection before writing specifications on this product.

Test*	Property	Unit	Result
CTM 0176	Color		Coral
CTM 0517	Rebound	%	70
CTM 0166	Plasticity		70-105
CTM 0022	Specific gravity, at 25°C (77°F)		1.10-1.18
CTM 0495	Slump	inches	0.75

\*CTM: Corporate Test Method, copies of CTMs are available on request.

#### DESCRIPTION

Dow Corning® 3179 Dilatant Compound is a coral-colored silicone polymer that exhibits high elasticity, high bounce and a unique combination of rheological properties. It offers ease of movement under low mechanical force and yet exhibits excellent resistance to slump or flow when at rest.

#### **HOW TO USE**

Dow Corning 3179 Dilatant Compound is designed specifically for the novelty toy market for use by children to bounce, stretch and snap. Its non-slumping characteristic offers an additional dimension to this product. It can be used to mold simple shapes such as cubes, rectangles and pyramids and retain these shapes for weeks, a feature that can expand the scope of this product from the novelty to the educational. This resistance to static flow in combination with ease of manipulation is a feature of Dow Corning 3179 Dilatant Compound.

#### **PERFORMANCE**

#### Cleanup

If *Dow Corning* 3179 Dilatant Compound is worked into material or carpets, it may be removed by the careful application of 95 percent isopropyl alcohol and repeated blotting or brushing. As with all stain removal, check for colorfastness and resistance to fiber damage before applying isopropyl alcohol to an exposed area of the material.

NOTE: Always provide adequate ventilation when using any volatile solvent. Avoid heat, sparks and open flame. Follow all precaution listed on solvent container label.

HANDLING PRECAUTIONS
PRODUCT SAFETY
INFORMATION REQUIRED FOR
SAFE USE IS NOT INCLUDED IN
THIS DOCUMENT. BEFORE
HANDLING, READ PRODUCT
AND MATERIAL SAFETY DATA
SHEETS AND CONTAINER
LABELS FOR SAFE USE,
PHYSICAL AND HEALTH

HAZARD INFORMATION. THE MATERIAL SAFETY DATA SHEET IS AVAILABLE ON THE DOW CORNING WEB SITE AT DOW CORNING.COM, OR FROM YOUR DOW CORNING SALES APPLICATION ENGINEER, OR DISTRIBUTOR, OR BY CALLING DOW CORNING CUSTOMER SERVICE.

### USABLE LIFE AND STORAGE

When stored at or below 40°C (104°F), *Dow Corning* 3179 Dilatant Compound has a shelf life of 24 months from date of shipment.

#### PACKAGING INFORMATION

This product is available in different standard container sizes. Detailed container size information should be obtained from your nearest Dow Corning sales office or Dow Corning distributor.

#### **LIMITATIONS**

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

#### HEALTH AND ENVIRONMENTAL INFORMATION

To support Customers in their product safety needs, Dow Corning has an extensive Product Stewardship organization and a team of Product Safety and Regulatory Compliance (PS&RC) specialists available in each area.

For further information, please see our Web site, dowcorning.com or consult your local Dow Corning representative.

#### LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow Corning's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

DOW CORNING SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

DOW CORNING DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

We help you invent the future. TM

dowcorning.com